

NBP 2027P/2027S

20 slot backplane

SPECIFICATIONS

System architecture

20 slots backplane, 2 segments, 3 PICMG and 7PCI slots for each segment

Dimension

415(w) x 260(L) mm

Connector

AT / ATX special connector x 2

KEYBOARD x 4

FAN PIN x 4

WAKE UP PIN x 2

POWER ON/OFF x 2

TERMINAL BLOCK x 2

LED 5 x 2 sets (+5,-5, +12,-12, +3.3V)

P-VIO setting switch x 1

S-VIO setting switch x 1

Chipset

Pericom Bridge PI7C8150MA

Segment

2 segments and independent power on/off control

Board

4 Layers, 2.0 mm thickness board

Environments

Operating temperatures: 0°C to 60°C

Storage temperatures: -20°C to 80°C

Relative humidity: 10% to 90% (Non-condensing)

Certification

CE

FCC class A

Anewtech Systems

ANEWTECH SYSTEMS PTE LTD

52 Kallang Bahru #03-17/18 Kallang Basin Industrial Estate Singapore 339335

Tel: (65) 6292 0801 Fax: (65) 6292 0831 Email: sales@anewtech.com.sg

ANEWTECH SYSTEMS SDN BHD

31B Jalan SS4D/2, 47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia

Tel: (603) 7880 1480 Fax: (603) 7880 1476 Email: anewtech@tm.net.my

Website: <http://www.anewtech.net>

