EC-1040	4U Full Function IPC Chassis Complete Function in a 4U Chassis

SPECIFICATIONS

LCD SIZE	6.4" TFT
HEIGHT & EXPANSION SLOT	4U 14-slot or ATX MB
PANEL TYPE	PRIME VIEW-V16C6448AC
LCD INTERFACE	Analog VGA Input
MAX.RESOLUTION	640x480
BRIGHTNESS	300 cd/m²
LCD COLOR	262K
VIEW ANGLE	H-V 170(H)x30(V)
LCD MTBF	50,000hrs
BACKLIGHT MTBF	25, 000hrs
CONSTRUCTION FRONT PANEL	Plastic
CONSTRUCTION CHASSIS	Heavy-duty steel
OSD CONTROL KEY	YES
HDD DRIVE BAY	N/A
FDD DRIVE BAY	1x3.5" FDD
CD-ROM DRIVE BAY	3x5.25" CD-ROM
KEYBOARD	KM-085 or KM-088
POWER SUPPLY	ACE-832A (AC Input 300W ATX)
	ACE-R30A (AC Input 300W Redundant ATX)
	PS/2 AC/DC Input AT/ATX
MOUNTING	RACK mount
DIMENSION(WxDxH) mm	431x480x176
OPERATION TEMPERATURE	0~50ºC

Anewtech Systems

ANEWTECH SYSTEMS PTE LTD
52 Kallang Bahru #03-17/18 Kallang Basin Industrial Estate Singapore 339335
Tel: (65) 6292 0801 Fax: (65) 6292 0831 Email: sales@anewtech.com.sg
ANEWTECH SYSTEMS SDN BHD
31B Jalan SS4D/2, 47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel: (603) 7880 1480 Fax: (603) 7880 1476 Email: anewtech@tm.net.my
Website: http://www.anewtech.net

SPECIFICATIONS | EC-1040

SUPPORT SLIDE	24" or 18"
VIBRATION	5~17Hz
	17~640Hz 1.5G acceleration peak to peak
	0.1” double amplitude displacement
SHOCK	10G acceleration peak to peak (11ms)
NET/GW	13/20 (kg)
TOUCH SCREEN	T-R064B (6.4" Resistive type)

* Product color and specification may change without notice.
Please contact our sales representatives for updated product information.

Anewtech Systems
ANEWTECH SYSTEMS PTE LTD
52 Kallang Bahru #03-17/18 Kallang Basin Industrial Estate Singapore 339335
Tel: (65) 6292 0801 Fax: (65) 6292 0831 Email: sales@anewtech.com.sg
ANEWTECH SYSTEMS SDN BHD
31B Jalan SS4D/2, 47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel: (603) 7880 1480 Fax: (603) 7880 1476 Email: anewtech@tm.net.my
Website: http://www.anewtech.net