

Both tag series operate at the universally accepted HF frequency of 13.56 MHz and are fully compatible with the state-of-the art Cobalt HF™ RFID Controller/Antenna family from EMS.

## HMS-HT SERIES: 736 BYTE, PASSIVE TAGS



### HMS125HT

Size	25x5mm
Memory	736 Bytes
Frequency	13.56MHz
Air Protocol	EMS HMS
Storage Temp	-40 to 240 C
Operating Temp	-40 to 135 C
Protection Class	IP67
Read/Write Cycles:	
	100K+ Writes, Unlimited Reads, Data Retention 10 years

#### ANTENNA / CONTROLLER COMPATIBILITY:

C0405-Series  
C1007-Series  
HF-CNTL-Series  
HF-816  
HF-818  
HF-0405 Series  
Element™

### HMS150HT

Size	50x5mm
Memory	736 Bytes
Frequency	13.56MHz
Air Protocol	EMS HMS
Storage Temp	-40 to 240 C
Operating Temp	-20 to 135 C
Protection Class	IP67
Read/Write Cycles:	
	100K+ Writes, Unlimited Reads, Data Retention 10 years

#### ANTENNA / CONTROLLER COMPATIBILITY:

C0405-Series  
C1007-Series  
HF-CNTL-Series  
HF-816  
HF-818  
HF-0405 Series  
Element™