

JV264-004/008/016

Professional H.264 internet DVR



FEATURES

- Advanced H.264 compression.
- D1 resolution for Preview and Recording.
- Realtime Live View (30frame/NTSC, 25frame/PAL)
- Support 3G cell phone for high quality remote monitoring.
- Visualized Remote Application software.
- Provide eSATA port for Storage application.
- Network DDNS/ DHCP function
- Support Audio/ RS-485/ Sensor
- Advanced Central Management Software

DVR

SPECIFICATION		JV264-004	JV264-008	JV264-016
Video Input (NTSC/PAL)		4	8	16
Video Compression		Advanced H.264 Algorithm for saved file and internet transmission		
Video Output		Main output: BNC x1 , Spot output: BNCx1 , VGA x 1 (Option)		
Audio Input		RCA X 4		
Audio Output		RCA X 1		
Sensor In / Alarm Out		4 Sensor in / 1 Alarm out	8 Sensor in / 1 Alarm out	16 Sensor in / 1 Alarm out
Display	Speed	100/120 fps	200/240 fps	400/480 fps
	Resolution	720 x 480 (NTSC), 720 x 576 (PAL)		
	Split Screen	1/4/SEQ	1/4/6/8/SEQ	1/4/8/13/16/SEQ
	Mode	Zoom x 2, PIP, Auto SEQ		
Recording	Resolution (pixels)	NTSC: 720x480, 720x240, 360x240 (D1/Half-D1/CIF) PAL: 720x576, 720x288, 360x288 (D1/Half-D1/CIF)		
	Picture Quality	5 Levels (Highest, High, Normal, Low, Lowest)		
	Mode	Normal, Motion, Alarm, Sensor, Schedule, Holiday, Manual		
	Speed	NTSC: 60fps(720x480), 120fps(720x240), 240fps(360x240) PAL: 50fps(720x576), 100fps(720x288), 200fps(360x288)		
	Device	2 internal SATA HDDs or 1 SATA HDD & DVD-RW		3 SATA HDD or 2 SATA HDD & DVD-RW
	Display	1,4	1,4,8	1,4,8,16
Playback	Resolution	NTSC: 60fps(720x480), 120fps(720x240), 240fps(360x240) PAL: 50fps(720x576), 100fps(720x288), 200fps(360x288)		
	Search	Segment, Time, Event, Calendar		
	Speed	Normal, REW & FF(2x, 4x, 8x, 16x, 32x, 64x), Pause		
Pre-alarm Recording		16MB (10secs)		
Backup Device		USB 2.0, SATA CD Writer, SATA DVD writer, Remote Network Backup		
PTZ Control		Pelco P, Pelco D, Li-Lin, Dynacolor		
Network	Communication	TCP/IP, HTTP, DHCP, ADSL, Lan, DDNS		
	Remote View	IE browser, 3G cell phone (Windows Mobile 5.0/6.0 and Symbian)		
	Remote Operation	Visualized AP(The same as Local DVR UI), Central management software		
	Users	5 Users allowed to log on DVR simultaneously with independent operation		
	Event Notification	Emails (up to 10 setting/ Gmail supported), MSN message		
Image format output		H.264		
OSD		GUI (Graphical user interface)		
DVR control		Remote Control, USB Mouse, USB Touch Panel		
Recovery		Watchdog		
Language		Chinese, English, Spanish, Greek, French, Portuguese, Russian, Japanese, German, Italian		
Dimension		430x293x55 mm		
Power		External Adaptor, AC100-240V/in, DC12V(5A)		