

RGS-R9244GP+ Series



RGS-R9244GP+ Series

➤ Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket

Features

- Supports Layer 3 routing, RIP and static routing function
- Support **O-Ring** (recovery time < 30ms over 250 units of connection) and MSTP(RSTP/STP compatible) for Ethernet Redundancy
- **O-Chain** allow multiple redundant network rings
- Support standard IEC 62439-2 **MRP^{*NOTE}** (Media Redundancy Protocol) function
- Support IPv6 new internet protocol version
- Support Modbus TCP protocol
- Support IEEE 802.3az **Energy-Efficient Ethernet** technology
- Provided HTTPS/SSH protocol to enhance network security
- Support SMTP client and NTP server protocol
- Support IP-based bandwidth management
- Support application-based QoS management
- Support Device Binding security function
- Support DOS/DDOS auto prevention
- IGMP v2/v3 (IGMP snooping support) for filtering multicast traffic
- Support SNMP v1/v2c/v3 & RMON & 802.1Q VLAN Network Management
- Support ACL and 802.1x User Authentication for security
- Supports 9.6K Bytes Jumbo Frame
- SFP socket support DDM function
- Multiple notification for warning of unexpected event
- Support **DBU-01** backup unit device to quickly backup/restore configuration
- Web-based, Telnet, Console (CLI), and Windows utility (**Open-Vision**) configuration
- Support LLDP Protocol
- 19 inches rack mountable design



Introduction


RGS-R9244GP+ series are Layer-3 Gigabit managed redundant ring Ethernet switch with 24x10/100/1000Base-T(X) ports and 4x1G/10GBase-X SFP+ ports. These switches support Layer-3 function like RIP and static routing. Also RGS-R9244GP+ series support Ethernet Redundancy protocol, O-Ring (recovery time < 30ms over 250 units of connection) /Open-Ring/O-Chain/MRP^{*NOTE}/Fast Recovery and MSTP (RSTP/STP compatible) can protect your mission-critical applications from network interruptions or temporary malfunctions with its fast recovery technology. RGS-R9244GP+ series support wide operating temperature from -20°C to 60°C. RGS-R9244GP+ series can also be managed centralized and convenient by Open-Vision as well as the Web-based interface, Telnet and console (CLI) configuration. Therefore, the switch is one of the most reliable choice for highly-managed and Fiber Ethernet application.

- **O-Ring** : O-Ring is ORing's proprietary redundant ring technology, with recovery time of less 30 milliseconds and up to 250 nodes. The O-Ring redundant ring technology can protect mission-critical application from network interruptions or temporary malfunction with its fast recover technology.
- **Open-Ring** : Open-Ring is an enhanced redundant technology that makes ORing's switches compatible with other vendor's proprietary redundant ring technologies. It enables ORing's switches to form a single ring with other vendor's switch. In cases where the ring is setup using proprietary technology, ORing offers a compatibility service where ORing can make its switches compatible with your particular network requirements.
- **O-Chain** : O-Chain is the revolutionary network redundancy technology that provides the add-on network redundancy topology for any backbone network, O-Chain allows multiple redundant network rings of different redundancy protocols to join and function together as a larger and more robust compound

*NOTE: This function is available by request only


network topology. O-Chain providing ease-of-use while maximizing fault-recovery swiftness, flexibility, compatibility, and cost-effectiveness in one set of network redundancy topology.

- **MRP^{NOTE}** : Media Redundancy Protocol (MRP) is a data network protocol standardized by the IEC 62439-2. It allows rings of Ethernet switches to overcome any single failure with recovery time much faster than achievable with Spanning Tree Protocol.
- **IP-based Bandwidth Management** : The switch provide advanced IP-based bandwidth management which can limit the maximum bandwidth for each IP device. User can configure IP camera and NVR with more bandwidth and limit other device bandwidth.
- **Application-Based QoS** : The switch also support application-based QoS. Application-based QoS can set highest priority for data stream according to TCP/UDP port number.
- **Device Binding Function** : ORing special Device Binding function can only permit allowed IP address with MAC address to access the network. Hacker cannot access the IP surveillance network without permission. It can avoid hacker from stealing video privacy data and attacking IP camera, NVR and controllers.
- **Advanced DOS/DDOS Auto Prevention** : The switch also provided advanced DOS/DDOS auto prevention. If there is any IP flow become big in short time, the switch will lock the source IP address for certain time to prevent the attack. It's hardware based prevention so it can prevent DOS/DDOS attack immediately and completely.
- **Modbus TCP** : This is a Modbus variant used for communications over TCP/IP networks.
- **IEEE 802.3az Energy-Efficient Ethernet** : This is a set of enhancements to the twisted-pair and backplane Ethernet family of networking standards that will allow for less power consumption during periods of low data activity. The intention was to reduce power consumption by 50% or more.




Open-Vision


ORing's switches are intelligent switches. Different from other traditional redundant switches, ORing provides a set of Windows utility (Open-Vision) for user to manage and monitor all of industrial Ethernet switches on the industrial network.



Commander




Host Monitor



Topology View

*NOTE: This function is available by request only

Dimensions



(Unit=mm)

Specifications

ORing Switch Model	RGS-R9244GP+	RGS-R9244GP+-E
Physical Ports		
10/100/1000Base-T(X) with RJ45 Auto MDI/MDIX		24
1G/10GBase-X with SFP+ port		4
Technology		
Ethernet Standards	IEEE 802.3 for 10Base-T IEEE 802.3u for 100Base-TX IEEE 802.3ab for 1000Base-T IEEE 802.z for 1000Base-X IEEE 802.3ae for 10Gigabit Ethernet IEEE 802.3x for Flow control IEEE 802.3ad for LACP (Link Aggregation Control Protocol) IEEE 802.1p for COS (Class of Service) IEEE 802.1Q for VLAN Tagging IEEE 802.1w for RSTP (Rapid Spanning Tree Protocol) IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol) IEEE 802.1x for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)	
MAC Table	8k	
Priority Queues	8	
Processing	Store-and-Forward	
Switch Properties	Switching latency: 7 us Switching bandwidth: 128Gbps Max. Number of Available VLANs: 4095 VLAN ID Range : VID 1 to 4094 IGMP multicast groups: 128 for each VLAN Port rate limiting: User Define	
Jumbo frame	Up to 9.6K Bytes	

Security Features	Device Binding security feature Enable/disable ports, MAC based port security Port based network access control (802.1x) Single 802.1x and Multiple 802.1x MAC-based authentication QoS assignment Guest VLAN MAC address limit VLAN (802.1Q) to segregate and secure network traffic Radius centralized password management SNMPv3 encrypted authentication and access security Https / SSH enhance network security Web and CLI authentication and authorization IP source guard	
Software Features	Hardware routing, RIP and static routing IEEE 802.1D Bridge, auto MAC address learning/aging and MAC address (static) Multiple Registration Protocol (MRP) MSTP (RSTP/STP compatible) Redundant Ring (O-Ring) with recovery time less than 30ms over 250 units TOS/Diffserv supported Quality of Service (802.1p) for real-time traffic VLAN (802.1Q) with VLAN tagging IGMP v2/v3 Snooping IP-based bandwidth management Application-based QoS management DOS/DDOS auto prevention Port configuration, status, statistics, monitoring, security DHCP Server/Client DHCP Relay Modbus TCP SMTP Client NTP server	
Network Redundancy	O-Ring O-Chain MRP**NOTE MSTP (RSTP/STP compatible) Fast Recovery	
RS-232 Serial Console Port	RS-232 in DB-9 connector with console cable. 115200bps, 8, N, 1	
LED Indicators		
Power Indicator (PWR)	Green : Power indicator	
Ring Master Indicator (R.M.)	Green : Indicates that the system is operating in O-Ring Master mode	
O-Ring Indicator (Ring)	Green : Indicates that the system operating in O-Ring mode Green Blinking: Indicates that the Ring is broken.	
Fault Indicator (Fault)	Amber : Indicate unexpected event occurred	
10/100/1000Base-T(X) RJ45 Port Indicator	Green for Link/Act indicator. Dual color LED for speed indicator ~ Green for 1000Mbps / Amber for 100Mbps / Off-light for 10Mbps	
1G/10GBase-X SFP+ Port Indicator	Green for port Link/Act.	
Fault contact		
Relay	None	Present
Power		
Power Input	100 ~ 240VAC with power cord	100 ~ 240VAC with power cord, dual 36 ~ 72VDC power input
Power consumption (Typ.)	37.4W	37.4W
Overload current protection	Present	
Physical Characteristic		
Enclosure	19 inches rack mountable	
Dimension (W x D x H)	431 (W) x 342 (D) x 44 (H)mm (16.97 x 13.46 x 1.73 inch)	431 x 342 x 44mm (17 x 13.46 x 1.73 inch)
Weight (g)	4,597g	4,754g
MTBF(mean time between failures)		
Time	462,867hrs	371,822hrs
Environmental		

*NOTE: This function is available by request only

Storage Temperature	-40 to 85°C (-40 to 185°F)	
Operating Temperature	-20 to 60°C (-4 to 140°F)	
Operating Humidity	5% to 95% Non-condensing	
Regulatory approvals		
EMI	FCC Part 15, CISPR (EN55022) class A	
EMS	EN61000-4-2 (ESD), EN61000-4-4 (EFT), EN61000-4-6 (CS), EN61000-4-11	EN61000-4-3 (RS), EN61000-4-5 (Surge), EN61000-4-8,
Shock	IEC60068-2-27	
Free Fall	IEC60068-2-32	
Vibration	IEC60068-2-6	
Safety	EN60950-1	
Warranty	5 years	

Ordering Information

RGS-R9 AA B CCC - DD

Code Definition	10/100/1000Base-T(X) Port Number	Additional Port Number	Additional Port Type	Mode Type
Option	- 24 : 24 ports	- 4 : 4 ports	- GC+ : 1G / 10GBase-X, SFP+ socket	- E : enhanced model with dual DC inputs and one AC input

	Model Name	Description
Available Model	RGS-R9244GP+_US	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, US power cord
	RGS-R9244GP+_EU	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, EU power cord
	RGS-R9244GP+_UK	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, UK power cord
	RGS-R9244GP+_JP	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, JP power cord
	RGS-R9244GP+-E_US	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, US power cord
	RGS-R9244GP+-E_EU	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, EU power cord
	RGS-R9244GP+-E_UK	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, UK power cord
	RGS-R9244GP+-E_JP	Industrial Layer-3 28-port managed Gigabit Ethernet switch with 24x10/100/1000Base-T(X) and 4x1G/10GBase-X, SFP+ socket, JP power cord

Packing List

- RGS-R9244GP+/-E x 1
- Rack-mount Kit x 1
- ORing Tool CD x 1
- Power Cable x 1
- Quick Installation Guide x 1
- Console Cable x 1

Optional Accessories (Can be purchased separately)

- Open-Vision M500 : Powerful Network Management Windows Utility Suit, 500 IP devices
- DBU-01 : backup unit device
- SFP10G series : 1GMbps SFP optical transceiver
- SFP10G series : 10GMbps SFP optical transceiver