



Model		ANS-DV150	ANS-DV240	ANS-DV280	ANS-DV370	ANS-DV438
<b>LCD Panel SPEC</b>	Size	15.1"	24"	28"	37"	43.8"
	Panel type	TFT-LED back light				
	Resolution	1280 × 235	1920 × 360	1920 × 412	1920 × 540	1920 × 540
	Brightnees (typ)/(min)	300	400	500	500	500 nits
	Contrast(typ)	1500:1	1200:1	1400:1	4000:1	1000:1
	Response Time(ms)	10	10	10	10	10
	Visual angle	89(H)/89(V)	89(H)/89(V)	89(H)/89(V)	89(H)/89(V)	89(H)/89(V)
	Life(typ)	50,000 hrs (min.)				
	Active Area(mm)	374.78 × 64.5	597.6 × 107.23	698.4 × 150	885 × 249	1073.78 × 289.4
	Colour	8bit, 16.7 Million colors				
Port	USB2.0*2, HDMI*2, DP*1					
<b>Power</b>	Input Voltage	AC100 V ~ 240 V, 50-60 Hz				
	Power consumption(Watt)	≤20W	≤30W	≤40W	≤50W	≤60W
	Standby (Watt)	≤0.5W	≤0.5W	≤0.5W	≤0.5W	≤0.5W
<b>Environmental</b>	Working temperature (dC)	0°C~40°C				
	Storage temperature(dC)	-20°C~60°C				
	Storage humidity	10%~90% RH Non-Condensing				
	Working humidity	20%~80% RH Non-Condensing				
	The day longest time (hours/day)	18Hours				
<b>Other</b>	Speaker	10W * 2				
	Power Input	*1				
	Power I/O	*1				
<b>Structure</b>	<b>Dimension</b> (H x V x D) mm	402.58 × 91.8 × 26.2	627.56 × 144.97 × 17.5	728.4 × 180 × 35	895.1 × 256 × 21	1104.38 × 320 × 17.3
	Shell material	(NCT) Metal				
	Shell color	Black/silver frame				
	Wall mount hole site	N/A				

