


# PAC-700G *7-slot Half-size Compact Chassis*



**CD-ROM, and HDD are not included in package.**



### Easy hot-swappable fan



Step 1: Loosen the thumb screws  
Step 2: Pull the fan out gently  
Step 3: Unplug the power connector

## Features

- RoHS compliant design
- Two USB ports on the front panel
- One, 8 cm cooling fan with fan filter
- Easy access design for quick fan replacement
- Lockable door prevents unauthorized access


## Specifications

◆ Construction	Heavy duty metal
◆ SBC Form Factor	Half-size, slot CPU card
◆ Drive Combinations	2 x 5.25" + 1 x Front accessible 3.5" or 1 x 5.25" + 2 x Front accessible 3.5" or 1 x 5.25" + 1 x Front accessible 3.5" + 1 x 3.5" HDD
◆ Cooling Fans	1 x 8 cm
◆ I/O Ports	2 x USB on front panel
◆ I/O Openings	2 x LPT, 2 x COM
◆ Expansion Slots	7 slots
◆ Indicators	Power, HDD
◆ Buttons	Power switch, reset
◆ Operating Temperature	0°C ~ 50°C
◆ Operating Humidity	10% ~ 90%
◆ Color	B: Black
◆ Weight (Net/Gross)	6.2 kg/9 kg
◆ Dimensions (DxWxH)	279 mm x 321 mm x 176 mm

## Ordering Information

Part No.	Description
PAC-700GB-R11/BP-7S/916AP	7-slot half-size chassis, with BP-7S-RS-R30 and ACE-916AP-RS
PAC-700GB-R11/IP-7S/916AP	7-slot half-size chassis, with IP-7S-RS-R30 and ACE-916AP-RS
PAC-700GB-R11/A618A	7-slot half-size compact chassis, black, 1 x 8 cm fan, with ACE-A618A-RS-R11 (180W ATX model), RoHS

## Dimensions (Unit: mm)



## Backplane Options

Model No.	SBC Type	PCI	ISA	PCIe				PSU Connector
				x1	x4	x8	x16	
BP-7S-RS	ISA	0	7	0	0	0	0	AT
IP-7S-RS	PCISA	4	2	0	0	0	0	AT
IP-7SA-RS	PCISA	4	2	0	0	0	0	ATX
HPE-7S1	PCI/PICoE	4	0	2	0	0	0	ATX
HPXE2-7S1	HPCIE	3	0	0	0	2	0	ATX

## Power Supply Options

Type	Model No.	Watt
AT	ACE-916AP-RS	150W
	ACE-A618A-RS-R11	180W
ATX	ACE-A225A-R11	250W

PAC-700G supports single 1U height PSU. For more IIEI PSU models, please refer to section 5 or visit [www.ieiworld.com](http://www.ieiworld.com).