

iBOX Ultra 200 Series
iBOX-255H, iBOX-225H
Fanless Embedded BOX PC



KEY FEATURES

- Intel® Core™ Ultra processors (Arrow Lake-H)
- 2 x 262-pin CSO-DIMM DDR5 6400MHz up to 96GB (48GB per DIMM)
- 1 x USB4/Thunderbolt™4, 4 x USB3.2 Gen2, 2 x USB 2.0, 2 x M.2 Key M, 1 x M.2 Key E, 1 x COM, 1 x SATA3
- 2 x Intel 2.5 Gigabit LAN
- Supports Quad display, 2 x HDMI 2.1 TMDS, 1 x DP 2.1 (from USB4), 1 x DP 1.4a (from Type-C)
- Intel PTT
- Supports Intel® vPro, VMD RAID 0/1
- 19V Power Adapter
- OOB Function (BOM Optional)
- 200 x 176.6 x 53.6mm (7.87" x 6.95" x 2.11"), Fanless Embedded BOX PC

SPECIFICATIONS

Processor System	
CPU	Intel® Core™ Ultra processors (Arrow Lake-H) iBOX-255H (Ultra 7 255H, 6P+8E) iBOX-225H (Ultra 5 225H, 4P+8E)
Chipset	MCP
BIOS	AMI SPI 256 Mbit
Memory	
Technology	Dual Channel DDR5 6400MHz
Capacity	96GB (48GB per DIMM)
Socket	2 x 262-pin SO-DIMM
Graphics	
Controller	Intel® Graphics
HDMI	HDMI 2.1 TMDS Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 2.1/ 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Quad-Display (Included 2 outputs from Type-C)

Expansion Slot	
M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless
Audio	
Interface	Realtek ALC256, High Definition Audio.
Ethernet	
Controller/ Speed	LAN1: Intel I226LM with 10/100/1000/2500 Mbps, supports vPro LAN2: Intel I226V with 10/100/1000/2500 Mbps
Connector	2 x RJ-45
Storage	
M.2	1 x M.2 (KEY M, 2242) with PCIe Gen4 x4 for SSD 1 x M.2 (KEY M, 2242/2280) with PCIe Gen4 x4 for SSD
SATA	1 x SATA3.0 (6.0 Gb/s)
RAID	Intel® VMD RAID 0/1 **supported by identical interface (PCIe) PCIe interface: 2* M.2 Key M
Front I/O	
USB	1 x USB 3.2 Gen2 (Type A) 1 x USB4/Thunderbolt™ 4 (5V/3A, Supports DP 2.1 display output) 1 x USB3.2 Gen2 x2 (Type-C, 5V/3A, Supports DP1.4a display output) 2 x USB 2.0 *For Thunderbolt support, please refer to support list.
Audio	1 (headphone & microphone jack)
COM	1 x COM(RS-232/422/485)
Rear I/O	
HDMI	2 x HDMI 2.1 TMDS
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1
OOB	Supports Remote Power On/Off/Reset (BOM Optional)
Watchdog Timer	
Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec
Power Requirements	
Input PWR	12V~24V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready
Environment	
Operating Temp	-20°C ~ 50°C with air flow 0.5~0.8 m/s (with extended temp. peripherals)
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%
Mechanical	
Construction	Aluminum housing
Mounting	VESA mount/Wall mount/Din-rail
Dimensions (L x W x H)	200 x 176.6 x 53.6mm (7.87" x 6.95" x 2.11")
Weight	Net Weight: 3Kg
Others	
OS Support	Windows 10/11
TPM	Intel® PTT
Certifications	CE, FCC
Packing List	1 x 19V Power Adapter 1 x Wall mount kit