

NUCS 1300/D4 BOX Series
NUCS BOX-1360P/D4 NUCS BOX-1340P/D4
Slim Type Fanned Box



KEY FEATURES

- Intel® 13th Gen (Raptor Lake-P) Core™ Processors
- 2 x 260-pin SO-DIMM DDR4 3200 MHz, up to 64GB
- 1 x USB4, 5 x USB 3.2 Gen2, 1 x M.2 Key M, 1 x M.2 Key E (WiFi-6E Module)
- 1 x Intel 2.5 Gigabit LAN
- Supports Quad display, 2 x HDMI 2.0b, 2 x DP 1.4a (from Type-C)
- TPM 2.0 onboard IC
- 12V~19V DC-In
- 110.0 x 117.5 x 38mm, Slim Type Fanned Barebone

SPECIFICATIONS

Processor System	
CPU	Intel® 13th Gen (Raptor Lake-P) Core™ Processors NUCS BOX-1360P/D4(i7-1360P, 4P+8E) NUCS BOX-1340P/D4(i5-1340P, 4P+8E)
Chipset	MCP
BIOS	AMI SPI 256 Mbit
Memory	
Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM
Graphics	
Controller	Intel® Iris® Xe Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Quad-Display (Included 2 outputs from Type-C)

Expansion Slot	
M.2/ WLAN	1 x Wi-Fi 6E 802.11ax (2.4Gbps) + BT 5.2 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)

Audio	
Interface	Realtek ALC233, High Definition Audio.

Ethernet	
Controller/ Speed	Intel® I226LM with 10/100/1000/2500 Mbps
Connector	1 x RJ-45

Storage	
M.2	1 x M.2 (KEY M, 2242/2280) with PCIe Gen4 x4 for SSD

Front I/O	
USB	2 x USB 3.2 Gen2 (Type A) 1 x USB4 (Supports DP1.4a display output) 1 x USB3.2 Gen2 (Type-C, Supports DP1.4a display output)
Audio	1 (headphone & microphone jack)

Rear I/O	
HDMI	2 x HDMI 2.0b
Ethernet	1 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

Watchdog Timer	
Output Interval	From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec

Power Requirements	
Input PWR	12V~19V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment	
Operating Temp	0°C ~ 40°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Mechanical	
Construction	Plastic with sheet metal
Mounting	VESA mounting
Dimensions (W x D x H)	110.0 x 117.5 x 38mm
Weight	Net Weight:0.9Kg

Others	
OS Support	Windows 10/11
TPM	TPM 2.0 onboard IC
Certifications	CE, FCC
Packing List	1 x 19V/90W Power Adapter 1 x Screw Package 1 x VESA mounting bracket