

GPU SuperServer AS -A126GS-TNBR

DP AMD 10U System with NVIDIA HGX B200 8-GPU




Key Applications

High Performance Computing, AI/Deep Learning Training, Industrial Automation, Retail, Healthcare, Conversational AI, Business Intelligence & Analytics, Drug Discovery, Climate and Weather Modeling, Finance & Economics,

Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors;
- Support 8 onboard SXM GPU accelerator cards, air cooled;
- Support up to DDR5 24 DIMM slots (1DPC);
- 2 10G NIC (X710), 1 VGA, 2 USB 3.0, and 1 Dedicated IPMI;
- 8 PCIe 5.0 x16 LP + 2 PCIe 5.0 x16 FHHL slots;
- 8 front hot-swap 2.5" NVMe + 2 hot-swap 2.5" SATA drive bays (8 E1.S drive bays (optional));



Form Factor	<p>10U Rackmount</p> <p>Enclosure: 449 x 438.8 x 843.28mm (17.6" x 17.2" x 33.2")</p> <p>Package: 1255 x 640 x 694mm (49.4" x 25.2" x 27.3")</p>
Processor	<p>Dual processor(s)</p> <p>AMD EPYC™ 9005/9004 Series Processors</p> <p>Up to 384C/768T</p>
GPU	<p>Max GPU Count: Up to 8 onboard GPUs</p> <p>Supported GPU: NVIDIA SXM: HGX B200 8-GPU (180GB)</p> <p>CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect</p> <p>GPU-GPU Interconnect: NVIDIA® NVLink® with NVSwitch™</p>
System Memory	<p>Slot Count: 24 DIMM slots</p> <p>Max Memory (1DPC): Up to 9TB 6000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)</p> <p>Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)</p>
Drive Bays Configuration	<p>Default: Total 10 bays</p> <ul style="list-style-type: none"> • 8 front hot-swap 2.5" PCIe 5.0 x4 NVMe drive bays • 2 front hot-swap 2.5" SATA drive bays <p>Option A: Total 8 bays</p> <ul style="list-style-type: none"> • 8 front hot-swap E1.S NVMe* drive bays <p>(*NVMe support may require additional storage controller and/or cables, please see the optional parts list for details)</p> <p>M.2: 2 M.2 NVMe slots (M-key)</p>
Expansion Slots	<p>PCI-Express (PCIe) Configuration: Default</p> <ul style="list-style-type: none"> • 8 PCIe 5.0 x16 LP slots • 2 PCIe 5.0 x16 FHHL slots <p>M.2: 2 M.2 NVMe slots (M-key 22110(default))</p>
On-Board Devices	<p>Chipset: System on Chip</p> <p>Network Connectivity: 2 RJ45 10GbE with Intel® X710</p>
Input / Output	<p>LAN: 1 RJ45 1 GbE Dedicated BMC LAN port</p> <p>USB: 2 USB 3.0 Type-A ports(Rear)</p> <p>Video: 1 VGA port</p> <p>TPM: 1 TPM header</p>

System Cooling	Fans: 19x 8cm heavy duty fans with optimal fan speed control Air Shroud: 1 Air Shroud
Power Supply	6x 5250W Redundant Titanium (certification pending) Level (96%) power supplies
System BIOS	BIOS Type: AMI 64MB SPI Flash EEPROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 183 lbs (83.1 kg) Net Weight: 122.7 lbs (55.64 kg) Available Color: Silver
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H14DSG-OD
Chassis	CSE-GP1001TS-R000NPF