



GPU SuperServer SYS-221GE-TNHT-LCC

DP Intel 2U Liquid-Cooled System with NVIDIA HGX H100 4-GPU

Key Applications

High Performance Computing, AI/Deep Learning Training, Industrial Automation, Retail, Healthcare, Conversational AI, Business Intelligence & Analytics, Drug Discovery, Climate and Weather Modeling, Finance & Economics,

Key Features

- Highest GPU communication using NVIDIA® NVLINK™
High density 2U system with NVIDIA® HGX™ H100 4-GPU;
- 5th/4th Gen Intel® Xeon® Scalable processor support;
- 32 DIMM slots Up to 8TB: 32x 256 GB DRAM Memory Type: 5600MTs ECC DDR5;
- 4 PCIe Gen 5.0 X16 LP;
- Flexible networking options;
- 2 M.2 NVMe for boot drive only
4x 2.5" Hot-swap NVMe/SATA3 drive bays;
- Direct-To-Chip Liquid Cooling solution
4 heavy duty fans with optimal fan speed control;
- 2x 5250W(1+1) Redundant Power Supplies;



| | |
|--------------------------|--|
| Form Factor | 2U Rackmount Enclosure: 437 x 89 x 830.3mm (17.2" x 3.5" x 32.7") Package: (22.5" x 11" x 45.5") |
| Processor | Dual Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors Up to 56C/112T; Up to 112.5MB Cache per CPU |
| GPU | Max GPU Count: Up to 4 onboard GPUs Supported GPU: NVIDIA SXM: HGX H100 4-GPU (80GB) CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink® |
| System Memory | Slot Count: 32 DIMM slots/16 Channels Max Memory (2DPC): Up to 8TB 5600MT/s ECC DDR5 RDIMM/LRDIMM |
| Drive Bays Configuration | Default: Total 4 bays <ul style="list-style-type: none"> • 4 front hot-swap 2.5" NVMe/SATA drive bays |
| Expansion Slots | PCI-Express (PCIe) Configuration: Default <ul style="list-style-type: none"> • 4 PCIe 5.0 x16 LP slots M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 22110(default)/2280) |
| On-Board Devices | Chipset: Intel® C741 Network Connectivity: 2 RJ45 10GbE with Intel® X710-AT2 |
| Input / Output | 1 VGA port |

(Front View – System)



| Drive Bay | Description |
|---------------------------------------|-------------|
| 4 Hot-swap 2.5" NVMe/SATA3 Drive Bays | |

(Rear View – System)



| Slot | Description |
|-----------------|-------------|
| PCIe 5.0 x16 LP | |
| CPU1 CPU2 | |

| | |
|-----------------------|---|
| System Cooling | Fans: 4 Fan 8cm Fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional) |
| Power Supply | 2x 5250W Redundant Titanium (certification pending) Level (96%) power supplies |
| System BIOS | BIOS Type: AMI 32MB SPI Flash EEPROM |
| Management | SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New! |
| PC Health Monitoring | CPU: Monitors for CPU Cores, Chipset Voltages, Memory 8+4 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 86.5 lbs (39.2 kg) Net Weight: 67.5 lbs (30.6 kg) Available Color: Silver Body |
| Operating Environment | Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing) |
| Motherboard | Super X13DEG-R |
| Chassis | CSE-228G2TS-R5K25P |