

GPU SuperServer SYS-422GS-NBRT-LCC

DP Intel 4U Liquid-Cooled System with NVIDIA HGX B200 8-GPU (complete rack and onsite service are required)

Key Applications



Scientific Research, Conversational AI, Business Intelligence & Analytics, Drug Discovery, Finance Services and Fraud Detection, AI/Deep Learning Training and Inference, Large Language Model (LLM) and Generative AI, High Performance Computing (HPC), Autonomous Vehicle Technologies,

Key Features

- Complete liquid-cooled rack integration is required for purchase;
- Dual Intel® Xeon® 6700 series processors with P-cores;
- 8x Nvidia B200 GPUs, 1.4TB of GPU memory space;
- 32x DIMMs slots, RDIMM ECC DDR5;
- 8x PCIe 5.0 x16 LP + 2x PCIe 5.0 x16 FHHL slots;
- 8x front hot-swap E1.S + 2x M.2 NVMe drive bays;
- 2x 10GbE, 1x Dedicated BMC/IPMI;
- 4x Redundant 6600W Titanium Level power supplies;



Form Factor	4U Rackmount Enclosure: 448 x 174 x 991.4mm (17.6" x 6.85" x 39.03") Package: 1395 x 410 x 795mm (54.92" x 16.14" x 31.29")
Processor	Dual Socket E2 (LGA-4710) Intel® Xeon® 6700-series processors with P-cores
GPU	Max GPU Count: 8 onboard GPUs Supported GPU: NVIDIA SXM: HGX B200 8-GPU (180GB) CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink® with NVSwitch™
System Memory	Slot Count: 32 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM Max Memory (2DPC): Up to 8TB 5200MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 8 bays <ul style="list-style-type: none"> • 8 front hot-swap E1.S NVMe drive bays M.2: 2 M.2 NVMe slots (M-key)
Expansion Slots	Default <ul style="list-style-type: none"> • 8 PCIe 5.0 x16 LP slots • 2 PCIe 5.0 x16 FHHL slots
On-Board Devices	Chipset: System on Chip Network Connectivity: 2 RJ45 10GbE with Intel® X710-AT2
Input / Output	1 VGA port(Front) 1 Mini-DP port(Front)



System Cooling	<p>Fans: 6 Fan 80mm Fan(s)</p> <p>Liquid Cooling: Direct to Chip (D2C) Cold Plate</p>
Power Supply	4x 6600W Redundant (2 + 2) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 64MB UEFI
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	<p>CPU: Monitors for CPU Cores, Chipset Voltages, Memory</p> <p>8+4 Phase-switching voltage regulator</p> <p>FAN: Fans with tachometer monitoring</p> <p>Status monitor for speed control</p> <p>Pulse Width Modulated (PWM) fan connectors</p> <p>Temperature: Monitoring for CPU and chassis environment</p> <p>Thermal Control for fan connectors</p>
Dimensions and Weight	<p>Weight: Gross Weight: 280 lbs (127 kg)</p> <p>Net Weight: 236 lbs (107 kg)</p> <p>Available Color: Silver</p>
Operating Environment	<p>Operating Temperature: 10°C to 35°C (50°F to 95°F)</p> <p>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)</p> <p>Operating Relative Humidity: 8% to 90% (non-condensing)</p> <p>Non-operating Relative Humidity: 5% to 95% (non-condensing)</p>
Motherboard	Super X14DBG-LC+
Chassis	CSE-GP405TS-R000NP