

HPC-7140

1U Rackmount Server Chassis for MicroATX/ATX Server board with 4 x 3.5" Hot-swap Drive Bays



CE FCC

Features

- 1U rackmount server chassis supports MicroATX/ATX motherboard
- Four hot swap 3.5" SATA/SSD drive bays
- Supports 1U single
- Easy swap and anti-vibration FAN design
- Two front USB and one front COM ports

Specifications

Form Factor Support	MicroATX/ATX	
Expansion Slots	1 (Full Height / Half Length)	
Drive Bay	Slim ODD Bay	1 (ODD should be purchased separately)
	5.25" (front-accessible)	-
	3.5" (hot-swappable)	4 x SATAIII
	3.5" (internal)	-
	2.5" (hot-swappable)	Optional
Cooling	2.5" (internal)	-
	Chassis Fan	4 (4cm / 23CFM)
System Monitoring	Air Filter	-
	Chassis intrusion switch	Yes
Front I/O Interface	USB 2.0	2
	COM Ports	1
Miscellaneous	LED Indicators	System : Power, LAN1, LAN2, HDD, System Information HDD Tray: HDD Power and Activity LED
	Rear Panel	-
Environment	Operating	Non-Operating
	Temperature	0 ~ 35 °C (32 ~ 95 °F) -40 ~ 70 °C (-40 ~ 158 °F)
	Humidity	10 ~ 85% @ 40 °C non-condensing 10 ~ 95% @ 40 °C, non-condensing
Physical Characteristics	Vibration (5-500 Hz)	0.25Grms 0.5G
	Dimensions (W x H x D)	437 x 43 x 504 mm (17.2" x 1.7" x 19.85")

Front View



Rear View


Single Power Supply SKU



Note: If need to use 3.5" SAS 12Gb/s HDD or redundant power supply , please change model to HPC-8104 1U Chassis.

Dimensions

Unit: mm [inch]



Ordering Information

Part Number	Description
HPC-7140-00A1E	HPC-7140 1U 4 bays server chassis (w/o single power supply)

Packing List

Items	Quantity
Hot-Swap 3.5" HDD tray with SATA cable (Pre-install)	4
Accessory Box	1

Power Supply Options

Part Number	80 Plus Grade	Wattage	Type	Input
PS8-350FATX-GB	Gold	350W	Single	AC 100 ~ 240V (full range)
PS8-500FATX-GB	Gold	500W	Single	AC 100 ~ 240V (full range)

Optional Accessories

Part Number	Description
19Z0001156T000	1U IO Shield for ASMB-585/785
1960088060T001	1U IO Shield for ASMB-586/786
1960082347T000	1U IO Shield for ASMB-815
1960082348T000	1U IO Shield for ASMB-825
1703040150	Type Y of Peripheral B4P Power Connector
96CB-SATAPOWER-6P2	SATA POWER ADAPTER 6PIN TO BIG 4 PIN(G) for Slim ODD
AIMB-RF10F-01A1E	1U PCIe x16 to PCIe x16 Riser Card
1960094951N000	2.5" HDD Bracket for Swappable HDD Tray
9680016685	25.6" - 33" Rail Kit for HPC-7140

* Note:

1. HPC-7140 does not support AIMB series motherboards.
2. HPC-7140 only supports up to 30 °C when ASMB-825 has been installed.
3. When installing Slim ODD, purchasing 1703040150 is a MUST.