

# R17IT3S-MRM1

## 17" Intel® Core™ i7-1165G7 Marine Panel PC



### KEY FEATURES

- Intel® Core™ i7-1165G7 processor marine panel PC
- Dimming knob control backlight brightness from nearly 0% to 100%
- 9~36V DC power input acceptable
- Panel (flush) mount IP66 aluminum housing with powder coating design



### OVERVIEW



#### Reliable Computing Certified for Marine Applications

Winmate marine panel PCs are built and tested according to DNVGL-CG-0339 Standard, IEC60945, and IACS-E10 to meet the international regulatory requirements of the marine industry. Standard, IEC60945, and IACS-E10. Winmate performs in-house reliability test to ensure optimal performance in harsh maritime environments.



#### Safe Sailing at Bright Sun, Dusk, and Night

To face the challenges of sailing in different conditions, Winmate marine panel PCs suitable for day, dusk, and night settings. Our devices feature hyper dimming technology that can control backlight brightness linearly from nearly 0% to 100% by a dimming knob. At the same time, add an optional transfective film to enhance the visibility in an outdoor and bright ambiance environment.



#### Convenient Front Panel OSD Control and Dimming Knob

All the controls are located on the front panel OSD for fast access anytime. Dimming knob allows controlling backlight brightness from nearly 0% to 100%, designed for marine industry applications.



#### Survives All Weather Conditions

The rugged mechanical design of the Winmate marine panel PCs provides enhanced shock and vibration resistance. Also, the high power efficiency and low heat design guarantee for mission-critical deployment. Deploy Winmate marine panel PCs for the stability and longevity required your safe operations at sea in all weather conditions.



#### Peripheral Connectivity

Marine Panel PC feature-rich I/O connectivity for easy integration into various marine dock equipment.


### SPECIFICATIONS

Display			
Resolution	1280x1024	Size	17.0 inches
Contrast Ratio	1000:1	Panel Brightness	350.0 nits

View Angles	85,85,80,80	Active Area	337.920x270.336 mm
Touch / Glass	Resistive Touch Screen AR Glass (Optional)		
System Specification			
Processor	Intel Core i7-1165G7 2.8GHz (up to 4.7GHz)	Memory	1 x SO-DIMM, DDR4 2400 MHz, 4GB 8GB (Optional) 16GB (Optional) 32GB (Optional)
Storage	1 x M.2 M-Key 2280 NVMe SSD, 128GB 256GB (Optional) 512GB (Optional) 1TB (Optional) 2TB (Optional) 4TB (Optional)	Ethernet controller	2 x 2.5 Giga LAN RJ45 Connector
Operating System	*Note : Only Windows 11 support Wake on touch Windows 11 IoT Enterprise (64 bit) Windows 11 Pro 64 bit (Optional) Windows 10 IoT Enterprise (64 bit) (Optional)		
Environment			
Operating Humidity	5% to 95%	Operating Temperature	-15~55°C
Shock	15G, 11ms duration	Vibration	0.7g@DNVGL CG-0339 (Class A)
IP rating	IP66 (Front Side)		
Certification			
Certification	CE, FCC		
IO Ports			
USB Port	2 x USB 3.0	Serial Port	1 x RS232, 4 x RS232 or 4 x Isolation RS422/485 (Optional)
Video	1 x HDMI (Optional)	LAN	2 x RJ45-10/100/1000 Mbps
Mechanical			
Dimension	337.5 x 272 x 77.2 mm	Weight	8.4 kg
Mounting	VESA Mount/ Panel Mount	Enclosure	Metal Housing with Aluminum Bezel
Cooling System	Fanless Design	Cut out	405 x 356 mm
Accessory			
Accessory	Driver CD & User Manual 4 x M6 Black Screw Bolt with M6 Nut 1 x AC Adapter12V/ 84W 1 x Power Cord		
Power			
Power Rating	9~36V DC Input Acceptable	Consumption	65W (Typical)
Control			
Button	1 x Power Button 1 x Reset Button 1 x The Dimming Knob		

DIMENSIONS

UNIT:MM



**NOTE**

- 1.This is a simplified drawing and some components are not marked in detail.
- 2.Please contact our sales representative if you need further product information.
- 3.All specifications are subject to change without prior notice.
- 4.The product shown in this datasheet is a standard model.For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.